



XingYue Communication Technology Co.,Ltd.

Product Name: LTE Log Periodic Antenna

Product Model: XY114602

Electrical Specifications

Frequency Range	698-800MHz	800-960MHz	1710-2700MHz
Polarization Type	Vertical		
Gain	$7.5 \pm 1\text{dBi}$	$9 \pm 1\text{dBi}$	$11 \pm 1\text{dBi}$
VSWR	$\leq 1.8:1$	$\leq 1.5:1$	$\leq 1.5:1$
Horizontal Beamwidth	$70^\circ \pm 8^\circ$	$65^\circ \pm 8^\circ$	$60^\circ \pm 10^\circ$
Vertical Beamwidth	$45^\circ \pm 8^\circ$	$40^\circ \pm 8^\circ$	$40^\circ \pm 8^\circ$
Front-to-back Ratio	$\geq 13\text{dB}$	$\geq 15\text{dB}$	$\geq 16\text{dB}$
Input Impedance	50 Ω		
Max Power	50W		
Lightning Protection	DC Ground		

Mechanical Specifications

Connector Type	N Female
Dimensions (L*W*H)	407*211*62mm(16.0*8.3*2.4in)
Radiating Element Material	Aluminum
Reflector Material	Aluminum
Weight	0.95kg
Radome Material	UABS
Radome Color	White
Mounting Pole	$\phi 30 \sim 52 \text{ mm}$
Cable	RG58U
Operating Temperature	-40°C~60°C




Add: No.11 GuangMing new RD, DongCheng area, DongGuan City, China
Tel: +86 - 769-22333955 Fax: +86 - 769-22000020
E-mail: xingyue@xytx86.com Website: <http://xytx86.com>




XingYue Communication Technology Co.,Ltd.


Product Diagram:



Installation Guide:



Directional Pattern:



800MHz-H

800MHz-V

2200MHz-H

2200MHz-V

PS:

H: Horizontal Pattern

V: Vertical Pattern